MARINE VHF TRANSCEIVER COLOTIA MARINE VHF TRANSCEIVER RAPINE VHF TRANSCEIVE



PRESET BUTTON -SAVE YOUR FAVORITE CHANNELS!



COBRA® UNIQUE
REWIND-SAY-AGAIN™
FEATURE
(MISS A CALL? PLAY IT BACK
BY PUSHING ONE KEY)



LONGER TALK TIMES!



SELECTABLE POWER OUTPUT-1, 3 or 5 WATTS

Cobra Marine® Professional Series MR HH415 LI VP EU Features:

- Unique Compact Design
- Submersible to JIS7 Standards
- Tri-Watch
- Unlimited Channel Memory
- External Speaker/Mic Jack
- Selectable Power Output -1, 3 or 5 Watts
- Large Illuminated Display
- Signal Strength Meter (Transmit and Receive Signal Bars)
- Illuminated Function Keys
- Instant Channel 16
- Spring Loaded Belt Clip
- ATIS









RAPID CHARGER & ACCESSORIES INCLUDED

ACTUAL SIZE

MR HH415 LI VP EU





MARI	NF I	/HF	TRAI	VSCEL	VER
	A / 💳	# # I I			

Fautura	Benefit	Unit Specifications	
Feature		General	
1,3 or 5 Watts	Adjustable output power for short and long communication.	Number of Channels	All International, Canadian, U.S.A.,
International, Canada & U.S.A. Channels	Allows operation on any of the three (3) different channel maps established for these areas.	Channel Spacing	25 kHZ
Cobra® Exclusive Rewind-Say-Again™ Feature	Not quite sure if the call was for you? Push the REWIND key to play back up to the last 20	Modulation	5 kHz Max.
Costa Exclosive Rowling Say Again Fourier	seconds of audio. Other bonus recording features included.	Input Voltage Battery Life: 5:5:90 Stand-by	7.2 VDC
LiON Polymer Battery	Lithium-Ion Polymer Battery allows for longer talk times, more successful charging seasons and maintenance free operation.	Alkaline Battery 20 Hours@ 5 Watts	Included Battery 11 Hours @ 5 Watts
External Speaker/Microphone Jack	Connect Cobra speaker mic accessories for hip or body worn operation.	35 Hours @ 1 Watt	18.5 hours@ 1 Watt
Instant Channel 16	Instant access to channel 16 for emergency situations.	Battery Requirements Current Drain:	Cobra® Battery Pack CM 110-010
Unlimited Channel Memory	Allows programming of unlimited channels for easy retrieval or scanning.	Stand-by	40 mA
Tri-Watch	Monitors three (3) channels at once - Channel 16 and two (2) user	Receive	200 mA
	selected channels.	Transmit	1.8 A @ High Power 700 mA @ Low Power
Scan	Scan all channels to find conversations in progress.	Temperature Range	-20°C to 50°C
Memory Scan	Scan channels programmed in memory to find conversations in progress.	Unit Dimensions	4.8" x 2.4" x 1.4" (123 mm x 62 mm x 36 mm) Not including antenna
Signal Strength Meter	Shows the strength of the receiving and transmitting signal.		
Button/Key Lock	Locks function buttons/keys to eliminate accidental change of settings.	Unit Weight (Lbs)	8 oz. (228 g) Without batteries
Battery Tray With Charge Contacts	Allows charging of batteries by simply dropping in the cradle.	Receiver	
Illuminated Function Keys	Allows high visibility of function keys.	Frequency Range	156.050 to 163.275 MHz
		Receiver Type	Double Conversion Super-Heterodyne
Illuminated LCD Display:Large	Allows high visibiity of display. Up to 60% larger than the competition.	Sensitivity: 20 dB Quieting	0.35 uV
Selectable Key Tone Beep	Key press beeps can be turned off to silent operation.		
Battery Saver Circuitry	A unique circuit extends the life of the batteries. If there are no transmissions within 10 seconds, the unit will automatically switch to battery saver mode.	12 dB Sinad Adjacent Channel Selectivity	0.30 uV -60 dB
Battery Saver Circuitry 10 Selectable Call Tones	A unique circuit extends the life of the batteries. If there are no transmissions within 10 seconds, the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls.		
10 Selectable Call Tones	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it	Adjacent Channel Selectivity	-60 dB -60 dB
10 Selectable Call Tones Roger Beep Tone (selectable)	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The default is off.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output	-60 dB
10 Selectable Call Tones	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter	-60 dB -60 dB -60 dB 250 mW @ 8 Ohms
10 Selectable Call Tones Roger Beep Tone (selectable)	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The default is off.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range	-60 dB -60 dB -60 dB 250 mW @ 8 0hms
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The default is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power	-60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert®	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The default is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories AA Alkaline Battery Tray	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The detault is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power +/-10 ppm
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The default is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability FM Hum & Noise	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories AA Alkaline Battery Tray (CM 110-011)	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The detault is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power. * Note - Some competitive models only allow for partial power transmit using Alkaline batteries.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability FM Hum & Noise Packaging Specifications	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power +/-10 ppm
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories AA Alkaline Battery Tray	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The default is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power. * Note - Some competitive models only allow for partial power transmit using	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability FM Hum & Noise Packaging Specifications Individual Clam/Box Dimensions	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power +/-10 ppm 40 dB 14.0" H x 8.9" W x 3.3" D (356 mm x 226 mm x 84 mm)
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories AA Alkaline Battery Tray (CM 110-011) LiON Battery Pack (CM 110-010) Rapid-Charge Locking Desktop Charger	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The detault is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power. * Note - Some competitive models only allow for partial power transmit using Alkaline batteries.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability FM Hum & Noise Packaging Specifications Individual Clam/Box Dimensions Individual Clam/Box Weight	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power +/-10 ppm 40 dB 14.0" H x 8.9" W x 3.3" D (356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g)
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories AA Alkaline Battery Tray (CM 110-011) LiON Battery Pack (CM 110-010) Rapid-Charge Locking Desktop Charger (CM 110-008)	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The detault is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power. * Note - Some competitive models only allow for partial power transmit using Alkaline batteries.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability FM Hum & Noise Packaging Specifications Individual Clam/Box Dimensions Individual Clam/Box Weight Master Pack Qty.	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power +/-10 ppm 40 dB 14.0" H x 8.9" W x 3.3" D (356 mm x 226 mm x 84 mm)
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories AA Alkaline Battery Tray (CM 110-011) LiON Battery Pack (CM 110-010) Rapid-Charge Locking Desktop Charger (CM 110-008) Swiveling Spring Loaded Belt Clip	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The detault is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power. * Note - Some competitive models only allow for partial power transmit using Alkaline batteries.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability FM Hum & Noise Packaging Specifications Individual Clam/Box Dimensions Individual Clam/Box Weight Master Pack Qty. Master Pack Dimensions	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power +/-10 ppm 40 dB 14.0" H x 8.9" W x 3.3" D (356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g) 4 7.0" H x 22.0" W x 9.1" D (178 mm x 559 mm x 231mm)
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories AA Alkaline Battery Tray (CM 110-011) LiON Battery Pack (CM 110-010) Rapid-Charge Locking Desktop Charger (CM 110-008) Swiveling Spring Loaded Belt Clip (CM 240-003) Wrist Strap	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The default is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power. * Note - Some competitive models only allow for partial power transmit using Alkaline batteries. 1900 mAh High Capacity Lithium-Ion Battery allows for longer talk times, more successful charging. Allows charging of batteries at home, car or boat. 12 volt vehicle adapter, AC wall adapter and mounting hardware included. 3-4 Hour Charge. Vertical or horizontal mounting. Secures the radio while on the go. Commercial quality belt clip.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability FM Hum & Noise Packaging Specifications Individual Clam/Box Dimensions Individual Clam/Box Weight Master Pack Qty. Master Pack Weight	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power +/-10 ppm 40 dB 14.0" H x 8.9" W x 3.3" D (356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g) 4 7.0" H x 22.0" W x 9.1" D (178 mm x 559 mm x 231mm) 8 lbs., 12.0 oz. (3969 g)
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories AA Alkaline Battery Tray (CM 110-011) LiON Battery Pack (CM 110-010) Rapid-Charge Locking Desktop Charger (CM 110-008) Swiveling Spring Loaded Belt Clip (CM 240-003) Wrist Strap (CM 230-002)	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The detault is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power. * Note - Some competitive models only allow for partial power transmit using Alkaline batteries. 1900 mAh High Capacity Lithium-Ion Battery allows for longer talk times, more successful charging. Allows charging of batteries at home, car or boat. 12 volt vehicle adapter, AC wall adapter and mounting hardware included. 3-4 Hour Charge. Vertical or horizontal mounting. Secures the radio while on the go. Commercial quality belt clip.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability FM Hum & Noise Packaging Specifications Individual Clam/Box Dimensions Individual Clam/Box Weight Master Pack Qty. Master Pack Dimensions Master Pack Weight SKU #	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power +/-10 ppm 40 dB 14.0" H x 8.9" W x 3.3" D (356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g) 4 7.0" H x 22.0" W x 9.1" D (178 mm x 559 mm x 231mm) 8 lbs., 12.0 oz. (3969 g) MR HH415LI VP EU
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories AA Alkaline Battery Tray (CM 110-011) LiON Battery Pack (CM 110-010) Rapid-Charge Locking Desktop Charger (CM 110-008) Swiveling Spring Loaded Belt Clip (CM 240-003) Wrist Strap	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The default is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power. * Note - Some competitive models only allow for partial power transmit using Alkaline batteries. 1900 mAh High Capacity Lithium-Ion Battery allows for longer talk times, more successful charging. Allows charging of batteries at home, car or boat. 12 volt vehicle adapter, AC wall adapter and mounting hardware included. 3-4 Hour Charge. Vertical or horizontal mounting. Secures the radio while on the go. Commercial quality belt clip.	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability FM Hum & Noise Packaging Specifications Individual Clam/Box Dimensions Individual Clam/Box Weight Master Pack Qty. Master Pack Weight	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power +/-10 ppm 40 dB 14.0" H x 8.9" W x 3.3" D (356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g) 4 7.0" H x 22.0" W x 9.1" D (178 mm x 559 mm x 231mm) 8 lbs., 12.0 oz. (3969 g)
10 Selectable Call Tones Roger Beep Tone (selectable) Patented VibrAlert® Submersible Included Accessories AA Alkaline Battery Tray (CM 110-011) LiON Battery Pack (CM 110-010) Rapid-Charge Locking Desktop Charger (CM 110-008) Swiveling Spring Loaded Belt Clip (CM 240-003) Wrist Strap (CM 230-002) AC Adapter	onds, 'the unit will automatically switch to battery saver mode. Allows the user to differentiate between up to 10 different parties on incoming calls. Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The detault is off. Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments. Meets JIS7 standards; Submersible for 30 minutes in one meter deep water. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power. * Note - Some competitive models only allow for partial power transmit using Alkaline batteries. 1900 mAh High Capacity Lithium-Ion Battery allows for longer talk times, more successful charging. Allows charging of batteries at home, car or boat. 12 volt vehicle adapter, AC wall adapter and mounting hardware included. 3-4 Hour Charge. Vertical or horizontal mounting. Secures the radio while on the go. Commercial quality belt clip. For ease of carrying and securing while on the go. 220V AC Mains Adapter with EU and UK plugs. Allows for charging at home or on AC	Adjacent Channel Selectivity Intermodulation and Rejection Spurious & Image Rejection AF Output Transmitter Frequency Range RF Output Power Spurious Emissions Frequency Stability FM Hum & Noise Packaging Specifications Individual Clam/Box Dimensions Individual Clam/Box Weight Master Pack Qty. Master Pack Weight SKU # UPC #	-60 dB -60 dB -60 dB 250 mW @ 8 0hms 156.025 to 157.425 MHz 1, 3 or 5 Watts -60 dB @ High Power -55 dB @ Low Power +/-10 ppm 40 dB 14.0" H x 8.9" W x 3.3" D (356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g) 4 7.0" H x 22.0" W x 9.1" D (178 mm x 559 mm x 231mm) 8 lbs., 12.0 oz. (3969 g) MR HH415LI VP EU 0 28377 20108 0

Cobra®, CobraMarine®, Nothing comes close to a Cobra® and the snake design are registered trademarks of Cobra Electronics Corporation, USA. Cobra Electronics Corporation™ and Rewind-Say-Again™ are trademarks of Cobra Electronics Corporation, USA.

Features and specifications subject to change.